


**Part Number: H155A00**

**COAX RF H155 PVC**



### Product Description

COAX RF [1.4/3.9] H155 STRANDED PVC

### Technical Specifications

#### Product Overview

Environmental Space:	Indoor - Euroclass Eca
Suitable Applications:	50 Ohm low loss coaxial transmission cable designed according European Standard EN 50117-1; Operating frequencies between 5 and 6000 MHz

#### Physical Characteristics (Overall)

##### Conductor

Stranding	Material	Construction n x D	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
Stranded	BC - Bare Copper	19x0.28 mm	1.41 mm	0.03 mm	1

Conductor Count:	1
AWG Size:	16

##### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	Foamed Polyethylene	3.9 mm	0.15 mm

Insulation, Table Note:	Centricity min. 85%
-------------------------	---------------------

##### Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Aluminum / Polyester / Aluminum		2 mm			
Braid	2	Tinned copper	80 %		4.5 mm	0.25 mm	5 %

##### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	5.4 mm	0.2 mm

#### Construction and Dimensions

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

#### Electrical Characteristics

##### Conductor DCR

Max. Conductor Loop	Max. Inner Shield DCR	Max. Shield DCR
32.4 Ohm/1000ft	15.4 Ohm/km	17 Ohm/km

##### Capacitance

Capacitance Tolerance	Nom. Capacitance Conductor to Shield
3 pF/m	84 pF/m

##### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
50 Ohm	3 Ohm	Min. 40 dB

### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	2.5 dB/100m
50 MHz	6.9 dB/100m
100 MHz	9.1 dB/100m
230 MHz	13.4 dB/100m
400 MHz	18 dB/100m
800 MHz	26.1 dB/100m
862 MHz	27.3 dB/100m
1000 MHz	29.6 dB/100m
1350 MHz	34.9 dB/100m
1750 MHz	40.3 dB/100m
2150 MHz	46 dB/100m
2400 MHz	49.1 dB/100m
3000 MHz	56.3 dB/100m
3600 MHz	62.9 dB/100m
4200 MHz	69.1 dB/100m
4800 MHz	75.1 dB/100m
5400 MHz	80.8 dB/100m
6000 MHz	86.5 dB/100m

### Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
80 %	2 %

### High Freq

Element	Frequency [MHz]	Min. RL (Return Loss) [dB]
	5 - 30 MHz	20 dB
	30 - 470 MHz	20 dB
	470 - 1000 MHz	18 dB
	1000 - 2000 MHz	16 dB
	2000 - 3000 MHz	15 dB
for information only	3000 - 6000 MHz	15 dB

High Freq Table Note: In each frequency band, 3 peak values up to 4 dB lower are allowed

### Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	85 dB

### Voltage

Voltage Test Dielectric
2 kV DC

### Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-15°C To +70°C
Operating Temp Range:	-15°C To +70°C

### Mechanical Characteristics

Max Recommended Pulling Tension:	100 N
Min Bend Radius (W/o Pulling Strength):	60 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	5-50 N at 25 mm N

### Standards

CPR Euroclass:	Eca
CENELEC Compliance:	EN 50117-1, EN 50117-2-4 and EN 50290-2-20
RG Type:	58/U Type

### Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
-----------------------	---------------

## Part Number

---

### Variants

Item #	Color
H155A00.001000	GRAY
H155A00.00250	GRAY
H155A00.00252	GRAY
H155A00.00500	GRAY
H155A00.00505	GRAY
H155A00.009999	GRAY
H155A00.00B100	GRAY
H155A00.00B50	GRAY
H155A00.099999	GRAY

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.