ULTRA WAH UW300

Ultimate Auto-Wah Effects Pedal

Thank you for showing your confidence in us by purchasing the BEHRINGER ULTRA WAH UW300. This high-quality effects pedal delivers auto-wah effects for almost all styles and sounds. Control the wah effect with your string-picking strength and add an awesome funky touch with the modulation wah pedal.

1. Controls



- 1 The **RATE** control determines the speed of the wah effect modulation.
- The **DEPTH** control adjusts the sweep range of the effect. Turn it to the right to increase the range. At minimum position no modulation effect is produced and the wah effect is controlled by your playing intensity only. In this case the RATE control has no function.
- The MANUAL control adjusts the basic frequency where the effect starts working. High MANUAL settings will decrease the sweep range, because the low end of the frequency sweep is moved upwards.
- The SENS control adjusts the sensitivity of the effect. Nearer maximum position you achieve wah effect even with soft playing, nearer minimum position the wah effect will not be dependent on your playing dynamics.
- The ON/BATT LED illuminates when the effect is activated. It also serves as a battery level indicator.
- 6 Use the footswitch to activate/deactivate the effect.
- Use this ¼" TS **IN** connector to plug in the instrument cable.
- 8 The ¼" TS **OUT** connector sends the signal to your amp.

Use the **DC IN** connection to plug in a 9 V power supply (not included).

The **BATTERY COMPARTMENT** is located underneath the pedal cover. To install or replace the 9 V battery (not included), press the hinges with a ballpoint pen and remove the pedal cover. Be careful not to scratch the unit.



The UW300 has no on/off switch. As soon as you insert the plug into the in connector, the UW300 is on. When not in use, remove the plug from the in connector. This extends the life of the battery.

The **SERIAL NUMBER** is located at the underside.

2. Safety Instructions

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

3. Warranty

Please register your new BEHRINGER equipment right after your purchase by visiting http://behringer.com and read the terms and conditions of our warranty carefully.

4. Specifications

In	
Connector	1⁄4" TS
Impedance	500 kΩ
Out	
Connector	1⁄4" TS
Impedance	1 kΩ
Power Supply	9 V ····, 100 mA regulated
BEHRINGER PSU-SB	-
USA/Canada	120 V~, 60 Hz
Europe/U.K./ Australia	230 V~, 50 Hz
China	220 V~, 50 Hz
Korea	220 V~, 60 Hz
Japan	

Power connector	2 mm DC jack, negative center
Battery	9 V type 6LR61
Power consumption	30 mA

Physical/Weight	
Dimensions (H x W x D)	approx. 2 ½ x 2 ¾ x 4 ½" approx. 54 x 70 x 123 mm
Weight	approx. 0.73 lbs / 0.33 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP.COM.). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HERRIC. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS AND RESERVED R

