


**Part Number: H500C00**

**COAX RF H500 PE**



## Product Description

COAX RF [2.5/7.0] H500 PE

## Technical Specifications

### Product Overview

Environmental Space:	Outdoor
Suitable Applications:	Coaxial cables used for Radio-Frequency designed according the International Standard IEC 1196

### Physical Characteristics (Overall)

#### Conductor

Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
Solid	BC - Bare Copper	2.5 mm	0.03 mm	1

Conductor Count:	1
AWG Size:	11

#### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	Foamed Polyethylene	7 mm	0.2 mm

Insulation, Table Note:	Centricity min. 85%
-------------------------	---------------------

#### Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Copper		2 mm			
Braid	2	Bare copper	50 %		7.45 mm	0.25 mm	5 %

#### Outer Jacket Material

Material	Nominal Diameter	Diameter - Tolerance
PE - Polyethylene	9.8 mm	0.3 mm

OuterJacket1, Table Note:	According to European Standard HD 624
---------------------------	---------------------------------------

### Construction and Dimensions

Min Elongation at Breakof Jacket:	300 %
Min Tensile Strength of Jacket:	10 MPa

### Electrical Characteristics

#### Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
3.8 Ohm/km	15.3 Ohm/1000ft	11.5 Ohm/km

#### Capacitance

Nom. Capacitance	Capacitance Tolerance
82 pF/m	3 pF/m

#### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
50 Ohm	2 Ohm	Min. 46 dB

## High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	0.9 dB/100m
50 MHz	2.9 dB/100m
100 MHz	4.1 dB/100m
200 MHz	6 dB/100m
400 MHz	8.7 dB/100m
600 MHz	10.9 dB/100m
800 MHz	12.9 dB/100m
1000 MHz	14.6 dB/100m
1350 MHz	17.4 dB/100m
1750 MHz	20.3 dB/100m
2150 MHz	23 dB/100m
2400 MHz	24.6 dB/100m
5000 MHz	38.9 dB/100m
10000 MHz	61.7 dB/100m

## Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
81 %	2 %

## Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	90 dB

## Voltage

Voltage Test Dielectric
3 kV DC

## Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

## Mechanical Characteristics

Bulk Cable Weight:	107 kg/km
Min Bend Radius (W/o Pulling Strength):	100 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	39-390 N at 50 mm N

## Standards

ISO/IEC Compliance:	IEC 1196
RG Type:	58/U Type

## Part Number

### Variants

Item #	Color
H500C00.002000	BLACK
H500C00.00250	BLACK
H500C00.00500	BLACK
H500C00.012000	BLACK
H500C00.00100	BLACK

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge.

information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.